

Thermatex EP

High performance high temperature industrial grease



Product description

Thermatex EP is a high performance, high temperature industrial grease designed to offer non-melting performance under extreme pressure, high temperature operations. Thermatex EP is formulated with highly refined ISO 100 mineral base stocks combined with an organoclay (bentonite) thickener. It is suitable for use in high temperature applications where frequent re-lubrication is available

Customer benefits and product features

Customer benefits

- Formulation offers non-melt performance, helping prevent grease loss and maintain lubrication under high temperature operation
- Wide temperature application from +135°C under normal conditions, and up to +260°C with very frequent re-lubrication
- Organoclay formulation offers reliable water washout and good equipment protection in wet operations

Product features

- Non-melt performance within a wide range of temperatures
- High temperature protection
- Wide temperature industrial application
- From +135°C under normal conditions, to +260°C with very frequent re-lubrication
- Water washout protection
- Selected specification standards include:
 - DIN
 - ISO

Applications

- Industrial ball and roller bearings in high temperature applications
- Exhaust fan bearings
- Furnace door bearings
- Kiln car wheel bearings
- Roll neck bearings
- High temperature conveyor bearings
- Rotary kiln bearings

Product approvals, performance and recommendations

	DIN 51 502	ISO 6743-09	Operating temperature
Thermatex EP 1	KP 1 N-20	ISO-L-XBDBB1	-20°C up to 135°C with frequent relubrication 260°C
Thermatex EP 2	KP 2 N-20	ISO-L-XBDBB2	

Thermatex EP

High performance high temperature industrial grease



Typical test data

THERMATEX EP	TEST METHODS	RESULTS	
NLGI Grade	DIN 51 818	1	2
Product Code		540817	540818
Thickener type	DIN 51 814	Bentone	Bentone
Thickener content, %	-	10	12
Dropping Point, °C	ISO 2176	NA	NA
Oil type	-	Mineral	Mineral
Base oil viscosity			
at 40°C, mm ² /s	DIN 51 562	92.5	92.5
at 100°C, mm ² /s	DIN 51 562	10.5	10.5
Penetration worked, 0.1 mm	ISO 2137	325	280
Copper Corrosion 24h/100°C	DIN 51 811	1B	1B
Timken OK load, kg	ASTM D2509	20	20

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Africa, Middle East and Pakistan.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

Thermatex EP/Asia Pacific/CHV/PDSv1_08/2024



A Chevron company product

© 2024 Chevron Products Company. Asia Pacific.
All Rights Reserved.